

Overview

The complete flowmeter system SITRANS FC330 can be ordered for standard, hygienic or NAMUR service. The flowmeter is based on the latest developments within digital signal processing technology – engineered for high measuring performance:

- Fast response to rapid changes in flow
- Fast dosing applications
- High immunity against process noise
- High turndown ratio of flowrates
- Suitable for liquid and gas service
- Easy to install, commission and maintain

With all global marine approvals the FC330 is ideal for integration in ship fuel efficiency and environmental measurement systems as well as bunkering solutions.

FC330 is available with current output HART 7.5, Modbus RS 485 RTU, PROFIBUS DP or PROFIBUS PA as standard on Channel 1. Additional functions can be freely configured for analog, pulse, frequency, relay or status output or binary input.

The transmitter comes with a user-configurable graphical display and SensorFlash, a micro SD card for configuration backup, firmware update and data storage.

The SITRANS FC330 flowmeter system consists of a SITRANS FCS300 sensor and a SITRANS FCT030 transmitter.

Benefits

- It is compact and light, fitting neatly into dense piping arrangements
- Easy maintenance because modules can be exchanged rapidly
- Effective separation of measurement from plant vibration
- Highly secure operation in safety critical applications
- Non-volatile memory of all setup and operation data
- Reliable measurements due to high signal to noise ratio
- Secure, digital transfer of measurement data from the sensor
- Short overall length; easy drop-in replacement into most existing installations

Flow Measurement

SITRANS FC (Coriolis)

Sensors and Flowmeter systems / SITRANS FC330 flowmeter system

Selection and ordering data

	Article No.	Order code
	7ME4633-	• • • • - • • • • • •
SITRANS FC330 digital Coriolis flowmeter with SITRANS FCS300 standard flow sensor compact or remote mounting with FCTO30 transmitter		
Click on the Article No. for the online configuration in the PIA Life Cycle Portal.		
Sensor size, connector size		
DN 15, DN 10 (1/2", 3/8")	3	F
DN 15, DN 15 (1/2", 1/2")	3	G
DN 15, DN 20 (1/2", 3/4")	3	H
DN 25, DN 20 (1", 3/4")	3	K
DN 25, DN 25 (1", 1")	3	L
DN 25, DN 40 (1", 1 1/2")	3	N
DN 50, DN 40 (2", 1 1/2")	4	B
DN 50, DN 50 (2", 2")	4	C
DN 50, DN 65 (2", 2 1/2")	4	D
DN 80, DN 65 (3", 2 1/2")	4	J
DN 80, DN 80 (3", 3")	4	K
DN 80, DN 100 (3", 4")	4	L
DN 100, DN 80 (4", 3")	5	M
DN 100, DN 100 (4", 4")	5	N
DN 100, DN 150 (4", 6")	5	Q
DN 150, DN 100 (6", 4")	6	D
DN 150, DN 150 (6", 6")	6	F
DN 150, DN 200 (6", 8")	6	H
Process connection		
EN 1092-1 B1, PN 16	A	0
EN 1092-1 B1, PN 40	A	1
EN 1092-1 B2, PN 63	A	2
EN 1092-1 B2, PN 100	A	3
EN 1092-1 D, PN 40	A	5
ASME B16.5 RF, Class 150	D	1
ASME B16.5 RF, Class 300	D	2
ASME B16.5 RF, Class 600	D	3
ASME B16.5 RF, Class 900 (p- and t-rating as Class 600)	D	4
ASME B16.5 RF, Class 1500 (p- and t-rating as Class 600)	D	5
ISO 228-1G female pipe thread	E	1
ASME B1.20.1 NPT female pipe thread	E	3
DIN 11851 hygienic screwed	F	1
DIN 32676 hygienic clamp (ISO) Row A	G	2
SMS 1145 hygienic screwed	K	1
JIS B2220/10K	L	2
JIS B2220/20K	L	4
EN 1092-1, PN 16, NAMUR length	N	1
EN 1092-1, PN 40, NAMUR length	N	2
Wetted parts material		
AISI 316L/1.4435/1.4404	1	
AISI 316L/1.4435/1.4404 (polished)	2	
Nickel alloy C4	3	
Calibration/Accuracy class		
0.2 % flow, 10 kg/m³ density	0	
0.1 % flow, 2 kg/m³ density	1	
0.1 % Standard fraction (with density 2 kg/m³)	8	
0.1 % Customer selected fraction	9	
		N 0 Y
Mounting style, transmitter housing and material		
None (replacement sensor)		A
Compact, IP67 fieldmount, aluminum		D
Remote, IP67 fieldmount, aluminum, M12		G
Remote, IP67 fieldmount, aluminum, T/Box		K
Remote, IP67, wall mount, aluminium (in preparation)		U
Ex approval (depending on variant)		
Non-Ex		A
ATEX (zone 1)		C

Selection and ordering data (continued)

	Article No. 7ME4633-	Order code
SITRANS FC330 digital Coriolis flowmeter with SITRANS FCS300 standard flow sensor compact or remote mounting with FCT030 transmitter	• • • • -	• • • • •
IECEx (zone 1)	F	
US (cCSAus), Div 1	L	
Canada (cCSAus), zone 1	M	
NEPSI	N	
INMETRO (in preparation)	P	
KCs	Q	
EAC Ex	U	
Local User Interface		
None (replacement sensor, DSL only)	0	
Blind	1	
Graphical, 240 x 160 pxl	3	

	Order code
Further designs Please add "-Z" to Article No. and specify Order code(s).	
Cable glands	
None (replacement sensor)	A00
Metric, no glands	A01
Metric, nylon, limited to -20 °C/-4 °F	A02
Metric, brass/Ni plated	A05
Metric, stainless steel	A06
NPT, no glands	A11
NPT, nylon, limited to -20 °C/-4 °F	A12
NPT, brass/Ni plated	A15
NPT, stainless steel	A16
Metric thread with M12 socket fitted	A20
Software functions and CT approvals	
None (replacement sensor)	B10
Standard	B11
I/O configuration Ch1	
No output channel	E00
4 ... 20 mA HART Active/Passive (non-Ex)	E02
Ca 4 ... 20 mA HART active (Ex)	E06
Ca 4 ... 20 mA HART passive (Ex)	E07
PROFIBUS PA	E10
PROFIBUS DP (non-Ex)	E11
Modbus RTU RS 485	E14
I/O configuration Ch2 (O), Ch3 (I/O) and Ch4 (I/O)	
None	F00
• Non Ex: Sig O, None, None. Active/passive menu selected	F01
• Non Ex: Sig O, Sig I/O, None. Active/passive menu selected	F02
• Non Ex: Sig O, Sig I/O, Sig I/O. Active/passive menu selected	F03
• Non Ex: Sig O, Sig I/O, R. Active/passive menu selected	F04
• Non Ex: Sig O, R, R. Active/passive menu selected	F05
• Non Ex: Sig O, R, None. Active/passive menu selected	F06
• Ex: pSig O, None, None	F11
• Ex: pSig O, pSig I/O, None	F12
• Ex: pSig O, pSig I/O, pSig I/O	F13
• Ex: pSig O, pSig I/O, R	F14

Flow Measurement

SITRANS FC (Coriolis)

Sensors and Flowmeter systems / SITRANS FC330 flowmeter system

Selection and ordering data (continued)

	Order code
• Ex: pSig O, R, R	F15
• Ex: pSig O, R, None	F16
• Ex: aSig O, None, None	F21
• Ex: aSig O, aSig I/O, None	F22
• Ex: aSig O, aSig I/O, aSig I/O	F23
• Ex: aSig O, aSig I/O, R	F24
• Ex: aSig O, R, R	F25
• Ex: aSig O, R, None	F26
Add-on options and accessories Please add "Z" to Article No. and specify Order code(s).	
Certificates	
Certificate EN 10204-2.2 confirmation of pressure containing material	C01
Certificate EN 10204-3.1 material (wetted parts)	C02
Certificate NACE MR0175-2009 + MR0103-2012	C04
Certificate EN 10204-2.1 Declaration of compliance with the order	C05
Insp. Certificate EN 10204-3.1 for visual, dimensional and functional test	C06
Certificate EN 10204-3.1 PMI Positive material ident. of pressure-cont./wetted parts (confirmation only)	C07
Certificate EN 10204-3.1 P-test Pressure-test acc. AD2000	C08
Test pack (pressure test, non-destructive welding test, welder & welding procedure certificate)	C09
Certificate EN10204-3.1 welding X-ray / Dye-penetration test of weldings (pressure cont.)	C10
Certificate EN10204-2.1 Declaration of accuracy	C11
Certificate EN10204-3.1 PMI Positive material ident. of pressure-cont./wetted parts (including heat analysis)	C12
Customer selected calibration	
DN 15 ... 50: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D60
DN 15 ... 50: Multi-point (10 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D61
DN 80: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D62
DN 80: Multi-point (10 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D63
DN 100: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D64
DN 100: Multi-point (10 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D65
DN 150: Multi-point (5 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D66
DN 150: Multi-point (8 flows × 1 pass) Flow 10 ... 100 % of Q _{norm}	D67
Cable	
None	L50
5 m (16.4 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L51
5 m (16.4 ft), sensor cable, 4 wire, without plugs for terminal connection	L52
10 m (32.8 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L55
10 m (32.8 ft), sensor cable, 4 wire, without plugs for terminal connection	L56

Selection and ordering data (continued)

Order code	
25 m (82 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L59
25 m (82 ft), sensor cable, 4 wire, without plugs for terminal connection	L60
50 m (164 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L63
50 m (164 ft), sensor cable, 4 wire, without plugs for terminal connection	L64
75 m (246 ft), sensor cable, 4 wire, with 2 pcs M12 plugs mounted	L67
75 m (246 ft), sensor cable, 4 wire, without plugs for terminal connection	L68
Sensor options	
FCS300 marine approval (in preparation)	S22
SD-Card accessibility via USB (not allowed in USA by Patent)	
Mass storage enabled	S30
Additional data Please add "-Z" to Article No. and specify Order code(s) and plain text.	
Tag name	
Tag name plate, stainless steel	Y17

Notes on I/O configurations:

a or p suffix: The I/O module is selected at ordering with either active or passive function.

Signal: The output can be selected for Current (0 or 4 to 20 mA), frequency or pulse function in the menu.

I: Discrete status input to the flowmeter. Functions are selected in the menu including 'Freeze output', 'Reset totalizer' (only CH3&4).

R: Relay output for discrete status reporting. Function is selected in the menu, including 'Error', 'High flow warning'.

The MLFB structure for FC330 systems must be filled to **this level**, including "-Z" options A.., B.., E.. and F.

Operating instructions for SITRANS FC330

Description	Article No.
English • for firmware V 4.0 and onwards	A5E44030648
German • for firmware V 4.0 and onwards	TBD

All literature is available to download for free, in a range of languages, at www.siemens.com/processinstrumentation/documentation

Flow Measurement

SITRANS FC (Coriolis)

Sensors and Flowmeter systems / SITRANS FC330 flowmeter system

Technical specifications

SITRANS FC330	
Sizes	DN 15 (1/2") DN 25 (1") DN 50 (2") DN 80 (3") DN 100 (4") DN 150 (6")
Accuracy	± 0.10 % or 0.20 % for liquids additional ± 0.40 for gases
Repeatability	± 0.05 %
Flow range (liquids) (water @ 1 bar pressure loss) (Q_{nom})	
• DN 15	4 500 kg/h (163.3 lb/min)
• DN 25	20 500 kg/h (753.2 lb/min)
• DN 50	49 000 kg/h (1 800 lb/min)
• DN 80	122 000 kg/h (4 483 lb/min)
• DN 100	273 000 kg (10 031 lb/min)
• DN 150	459 200 kg/h (16 873 lb/min)
Architecture	Compact or remote configuration
Display	Full graphical display, 240 x 160 pixels with selection of 6 languages
Power supply	20 ... 90 V DC ± 10%; 100 ... 240 V AC ± 10%, 47 ... 63 Hz ± 10 %
Material	
• Sensor	
- Wetted parts	316L stainless steel or nickel alloy C4 ¹⁾
- Enclosure	304 stainless steel
• Transmitter	Aluminum with corrosion-resistant coating class C4
Enclosure rating	IP67 ²⁾
Pressure ratings	
• Measuring tubes	
- 316L	100 bar (1 450 psi)
- Nickel alloy C4	100 bar (1 450 psi)
• Sensor enclosure	No pressure containment
Temperature ratings	
• Process medium	-50 ... +205 °C (-58 ... +400 °F)
• Ambient	-40 ... +60 °C (-40 ... +140 °F) ²⁾
• Display	-20 ... +60 °C (-4 ... +140 °F)
Process connections	
• Flanges	EN 1092-1 B1, EN 1092-1 B2, EN 1092-1 D, ANSI/ASME B16.5, JIS B 2220
• Pipe threads	ASME B1.20 (NPT) female pipe thread, ISO 228-1 G female pipe thread (BSPP)
• Hygienic threads	DIN 11851, SMS 1145
• Hygienic clamps	DIN 32676 (ISO) Row A
Approvals	
• Hazardous area (zone 1)	ATEX, IECEx, EAC Ex, CSA, cCSAus, NEPSI, EAC No dust approval
• Pressure equipment	PED, CRN
• Marine (in preparation for FC330 compact)	Germanischer Lloyd/det Norske Veritas, Bureau Veritas, Lloyds of London, American Bureau of Shipping, RINA (Italy)
NAMUR	NAMUR-compliant (e.g. NE 21, NE 41, NE 107 and NE 132)
I/O	Up to 4 channels combining analog, relay or digital outputs and binary input
Communication	<ul style="list-style-type: none"> • HART • PROFIBUS PA • PROFIBUS DP • Modbus RTU (RS 485)

Technical specifications (continued)

SITRANS FC330	
EMC performance	
Emission	EN 55011/CISPR-11 (Class A)
Immunity	EN/IEC 61326-1 (Industry)
Mechanical load	18 ... 400 Hz random The flowmeter will mechanically tolerate 3.17 g RMS in all directions. Flow accuracy cannot be guaranteed under all conditions.

- 1) Flange wetted parts and raised face surface in nickel alloy and non wetted parts in AISI 316L.
2) If operating outdoors, avoid direct sunlight, particularly in warm climatic regions.